


BLUEFIN II

Lynch Electric Outboard Motor



MARINE
ELECTRIC PROPULSION SYSTEMS



KEY FEATURES:

- ✓ 10-40HP (5-13KW) power.
- ✓ Suitable for 20-60ft boats.
- ✓ Lightweight - only 18KG.
- ✓ Powerful.
- ✓ Quiet and efficient.
- ✓ Easy to install and use.
- ✓ Includes controller unit.
- ✓ Includes battery monitor.
- ✓ Suited to a range of vessels

from pleasure, leisure & hire craft.

ALWAYS READY TO GO WHEN YOU ARE.



POWERFUL, RELIABLE
AND LIGHTWEIGHT
ELECTRIC MOTOR



REASONS TO SWITCH TO ELECTRIC

RELIABLE

ELECTRIC MOTOR STARTS EVERY TIME WITH A TURN OF THE KEY, ADJUST THE THROTTLE AND GO.

LOW FUEL COSTS

RECHARGE BATTERIES USING STANDARD PLUG OUTLET, SOLAR OR WIND.

EASY INSTALL

EASY TO INSTALL 'PLUG AND GO' SYSTEM.

POWERFUL

10-40HP (5-13KW)
IMMEDIATE POWER.
NO PRE-HEATING. EASY &
ACCURATE TO MANOEUVRE.

ECO FRIENDLY

QUIET AND CLEAN.
NO EXHAUST FUMES.
CLEAN ENGINE ROOM.
PEACEFUL AND TRANQUIL.
NO POLLUTION.
PLEASANT ENVIRONMENT.

SUITED FOR EMISSION
RESTRICTED WATERWAYS.

LIGHT WEIGHT

UP TO 10 X LIGHTER THAN
TRADITIONAL ENGINES.
JUST 18KG + CONTROL BOX.

IMPROVED CONTROL.
ENHANCED STEERING.
EXCELLENT POWER TO WEIGHT RATIO.
DISTRIBUTE BATTERIES FOR BETTER
WEIGHT OPTIMISATION.



Canal River Lake Sea

LOW MAINTENANCE COSTS

5,000 HASSLE FREE HOURS. TOP UP GEAR LUBRICANT. VISUAL
CHECKS OF BRUSHES. EASY AND INEXPENSIVE TO REPLACE.

BLUEFIN II

Lynch Electric Outboard

ALL LYNCH MARINE DRIVE SYSTEMS INCLUDE:

- ✓ ELECTRIC DC MOTOR
- ✓ CONTROLLER ASSEMBLY
- ✓ DISPLAY
- ✓ LEADS AND INSTALLATION MANUAL
- ✓ THROTTLE

2 YEAR
EXTENDABLE
WARRANTY

| TECHNICAL SPECIFICATIONS | BLUEFIN II 5 KW | BLUEFIN II 8 KW | BLUEFIN II 13 KW |
|--------------------------------|---------------------|---------------------|---------------------|
| REPLACE COMBUSTION ENGINE SIZE | 10-20 HP (20-30FT) | 17-25 HP (28-38FT) | 35-50 HP (35-60FT) |
| MOTOR SIZE | LEM 200-D135 | LEM 200-D135 | LEM 200-D135 |
| VOLTAGE | 48V | 48V | 72V DC |
| CURRENT | 140Amp | 180 Amp | 200 Amp |
| POWER OUTPUT | 5 KW | 8 KW | 13 KW |
| AVERAGE EFFICIENCY | 90% | 90% | 90% |
| BATTERY RECHARGE FUNCTION | YES | YES | YES |
| RATED SPEED ENGINE | 2160 RPM | 2160 RPM | 3240RPM |
| RATED TORQUE | 18 Nm | 36 Nm | 36 Nm |
| SPEED CONSTANT | 45 RPM/V | 45 RPM/V | 45 RPM/V |
| PEAK CURRENT | 350 Amp | 350 Amp | 400 Amp |
| PEAK POWER | 14 KW | 14 KW | 26 KW |
| PEAK TORQUE | 38 Nm | 44 Nm | 72 Nm |
| GEARING | To suit application | To suit application | To suit application |
| WEIGHT OF MOTOR AND FRAME | 18 KG | 18 KG | 18 KG |
| WEIGHT OF MOTOR CONTROL BOX | 12 KG - Medium Box | 12 KG - Medium Box | 14.5 KG - Large Box |

CONTROLLER ASSEMBLY

| CONTROLLER BOX SIZES |
|-------------------------------|
| MEDIUM - BLUEFIN II 5KW & 8KW |
| LARGE - BLUEFIN II 13KW |

DIMENSIONS (MM)

| | A | B | C |
|-------------------------------|--------|-----|--------|
| MEDIUM - BLUEFIN II 5KW & 8KW | 362.45 | 410 | 156.53 |
| LARGE - BLUEFIN II 13KW | 362.45 | 410 | 156.53 |



OPTIONS FOR DISPLAY AND THROTTLE - REMOTE STEERING

BASIC DISPLAY

System ON/OFF and direction switches with battery. Stainless steel backplate.

BMV 700 INTELLIGENT DISPLAY

Key ignition with voltage, battery capacity and available range. *Now with stainless steel backplate.

SIGMA DISPLAY

Key ignition with battery capacity levels, throttle settings and programme codes for controller.

STANDARD THROTTLE

One direction setting or neutral position with forward and reverse. Can be top or side mounted.

ZF THROTTLE

Neutral with forward and reverse only.



CONTACT US OFFICIAL DISTRIBUTOR